

COIL-OVER SHOCKS

Part Number	Extended Length	Collapsed Length w/out Bumper	Recommended Ride Height	*Stroke	Suggested Spring Length	External Adjustment Type
S5207	19.15"	12.64"	15.25"-16.00"	6.52"	14"	Single
S5007	19.15"	12.64"	15.25"-16.00"	6.52"	14"	Double
S5206	17.15"	11.64"	13.875"-14.50"	5.52"	12"	Single
S5006	17.15"	11.64"	13.875"-14.50"	5.52"	12"	Double
S5205	15.40"	10.76"	12.625"-13.250"	4.64"	12"	Single
S5005	15.40"	10.76"	12.625"-13.250"	4.64"	12"	Double
S5204	13.84"	10.00"	11.750"-12.125"	3.86"	10"	Single
S5004	13.84"	10.00"	11.750"-12.125"	3.86"	10"	Double
S5203	12.84"	9.50"	11.00"-11.375"	3.36"	7"-8"	Single
S5003	12.84"	9.50"	11.00"-11.375"	3.36"	7"-8"	Double
S5202	11.36"	8.74"	10.00"-10.375"	2.62"	7"-8"	Single
S5002	11.36"	8.74"	10.00"-10.375"	2.62"	7"-8"	Double

* Note: Stroke is stated without the bump rubber to compare with other brands. Most manufacturers list stroke with out the bump rubber; however, the shock should never be used without the bump rubber. Deduct .563" from the listed stroke.



Strange SINGLE adjustable shocks include heat treated 1" wide high mis-alignment bearings (teflon lined are optional), spring seats, jam nut and inspection serial number. Strange coil-overs require 2.50" I.D. springs. Upon request, the 1" wide mis-alignment bearings may be replaced with either .50" or 1.50" wide bearings.

All Single Adjustable Aluminum Coil-Over Shocks
(each)... **\$169⁰⁰**

Strange DOUBLE adjustable shock PACKAGES include 1" teflon lined high mis-alignment bearings, spring seats, jam nuts, inspection serial number and **Hypercoil** springs with spring bearing kit. Upon request, the 1" wide mis-alignment bearings may be replaced with either .50" or 1.50" wide bearings.

All Double Adjustable Aluminum Coil-Over Shock Packages
(Package)... **\$660⁰⁰**



S5000 Strange remote control kit. Includes: compressor, air lines, gauges and hardware... **\$247.50**

S500R7 Timer and circuit board for S5000 kit... **\$134.70**



S5000 (left)
S500R7 (right)

