

EVOLUTION 4-PISTON REAR BRAKE KIT INSTRUCTIONS

KIT #
B1722WCE
B1722WCEM

APPLICATIONS
04-94 Mustang OEM Ends using
A1094, 1095, 1096, 1097
Strange Eliminator Kits

Evolution Rotors

- Dynamic Drive Mount (DDM) system secures the rotor and allows for rotor thermal expansion
- DDM system design is secured by an internal Spirolox, eliminating heavy bolts and hardware
- Unique Aero Slot design reduces rotating weight and promotes even heat dissipation

Before you begin installation

Brake rotors are shipped with an oil film on surface to prevent rust and must be cleaned before installation.
Brake fittings do not come pre-installed, it will need a layer of Teflon sealer applied to the thread (Figure#1 for torque specs)
Read these instructions thoroughly and save for future reference.

If after reading these installation instructions, you have any questions or comments, please do not hesitate to call us.

KIT CONTENTS

ITEM#	PART#	QTY	DESCRIPTION
1	B2798AS	2	Evolution S Rotor
2	B2794B	2	2-Piece rotor adapter
3	B2794D	2	Spirolock
4	A1098G	2	Caliper mount O-ring
5	B1722A	2	05-14 Mustang caliper mount
6	B1301E	4	Press Nut
7	B1301H	16	0.025 Thick shim
8	B1900	2	Billet Caliper
9a	B5010	4	DTC-30 Semi metallic 4-piston brake pad (B1722WCE)
9b	B5020	4	DRM-35 metallic 4-piston brake pad (B1722WCEM)
9c	B5022	4	DRM-40 metallic 4-piston brake pad (B1722WCEM)
10	P2316	2	-1/8 NPT fitting
11	P2316C	2	Plastic Cap
12	B1301J	4	Washer 3/8 ID
13	B5000Z	4	3/8-24 x 1.187" HHCS

FIGURE # 1: B1722WCE Exploded view

Item#	Torque spec (ft-lbs)
Factory ABS sensor and Bolt	5
Factory safety hub bolts	35
8	25
10*	35

*Must apply red loctite

